

## mlsTrace Tool

```
/*
File:          mlsTrace tool User Manual
Authors:       Albert Myers, myers@uah.edu
               Aleksandar Milenkovic, milenkovic@computer.org
               LaCASA Laboratory
               The University of Alabama in Huntsville
Description:   This document describes the use and features of mlsTrace.
               mlsTrace is a Pin tool developed to capture and record
               memory reads and writes in multithreaded programs running under Pin.
               Each memory-referencing operation is captured and its
               descriptor is recorded into a trace file.

               IMPORTANT Note: If an instruction includes multiple memory operations,
               each operation will have a separate descriptor in the output trace.
               Intel64 instruction set includes instructions that can
               read one or two operands from memory, write the result to memory,
               or read from and write to memory. Instructions such as compare string
               can actually access a number of operands in memory.
               To avoid encoding inside a trace record we emit a trace descriptor
               for each memory access. Thus one instruction may have multiple
               trace records. Instruction set simulator should be able to replay
               the trace records correctly.

Date:          October 11, 2013
*/
```

## 1. Tool Setup (Compilation)

a) Requirements: Linux computer with Pin installed.

To learn more about Pin and to download the latest version visit

<http://software.intel.com/en-us/articles/pin-a-dynamic-binary-instrumentation-tool>.

Examples in this manual are prepared on a x86\_64 quad core machine running CentOS 6.3 OS with pin-2.12-58423.

b) Download source code files for mlsTrace:

mlsTrace.cpp

mlsTrace.h.

mlsTraceAssist.h

c) Copy source code files into Pin directory

pin-2.12-58423-gcc.4.4.7-linux/source/tools/ManualExamples

d) create obj-intel64 directory in

pin-2.12-58423-gcc.4.4.7-linux/source/tools/ManualExamples

e) Add mlsTrace to the TEST\_TOOL\_ROOTS line in

pin-2.12-58423-gcc.4.4.7-linux/source/tools/ManualExamples/makefile.rules

f) Add -std=c++0x to the TOOL\_CXXFLAGS\_NOOPT line in

pin-2.12-58423-gcc.4.4.7-linux/source/tools/Config/makefile.unix.config









